



DOCKET NO. 392.1681

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of:

Atsushi WATANABE, et al.

Serial No: 09/546,392

Group Art Unit: 2623

Confirmation No. 2369

Filed: April 10, 2000

Examiner: Hesseltine, Ryan J.

For: ROBOT SYSTEM HAVING IMAGE PROCESSING FUNCTION

RECEIVED

LETTER TO THE EXAMINER SUBMITTING  
CORRECTED FORMAL DRAWINGS

MAY 01 2003

Technology Center 2600

Assistant Commissioner for Patents  
Washington, D.C. 20231

ATTENTION: OFFICIAL DRAFTSPERSON

Sir:

In accordance with the requirement in Paper No(s). 9, mailed January 28, 2003, wherein the Examiner required that corrected formal drawings be filed responsive to the Examiner's requirement therefore in Paper No. 9, applicants herewith submit four (4) sheets of corrected formal drawings for filing in the subject application.

It is respectfully requested that the corrected formal drawings filed herewith be entered in the above-referenced application.

Respectfully submitted,

STAAS & HALSEY LLP

Date: 28 April 2003

By: James T. Strom

James T. Strom  
Registration No. 48,702


700 Eleventh Street, N.W., Suite 500  
Washington, D.C. 20001  
Telephone: (202) 434-1500  
Facsimile: (202) 434-1501



TITLE: ROBOT SYSTEM HAVING IMAGE  
PROCESSING FUNCTION  
INVENTORS: Atsushi WATANABE, et al.  
SERIAL NO.: 09/546,392  
DOCKET NO.: 392.1681

FIG. 4


(PRIOR ART)





TITLE: ROBOT SYSTEM HAVING IMAGE PROCESSING FUNCTION  
 INVENTORS: Atsushi WATANABE, et al.  
 SERIAL NO.: 09/546,392  
 DOCKET NO.: 392.1681

FIG. 6



QIPE  
JCA1  
APR 28 2003  
SEARCHED & TRADEMARK OFFICE


TITLE: ROBOT SYSTEM HAVING IMAGE  
PROCESSING FUNCTION  
INVENTORS: Atsushi WATANABE, et al.  
SERIAL NO.: 09/546,392  
DOCKET NO.: 392.1681

FIG. 7

REFERENCE MODEL NO. (M)	FIRST-SENSOR RELATIVE POSITION/POSTURE [RELATIVE POSITION POSTURE OF WORKPIECE WITH RESPECT TO CAMERA] (X, Y, Z, $\alpha$ , $\beta$ , $\gamma$ ) c	WORKPIECE-ROBOT RELATIVE POSITION/POSTURE [RELATIVE POSITION POSTURE OF SECOND VISUAL SENSOR TO BE SITUATED WITH RESPECT TO WORKPIECE] (X, Y, Z, $\alpha$ , $\beta$ , $\gamma$ ) wk
0	10.0, -20.8, 50.5, 0.0, 0.0, 0.0	35.5, 20.5, 60.9, 0.0, 0.0, 0.0
1	10.0, -20.8, 50.5, 30.0, 0.0, 0.0	35.5, 20.5, 60.9, 0.0, 0.0, 0.0
2	10.0, -20.8, 50.5, 60.0, 0.0, 0.0	35.5, 20.5, 60.9, 0.0, 0.0, 0.0
3	10.0, -20.8, 50.5, 90.0, 0.0, 0.0	35.5, 20.5, 60.9, 0.0, 0.0, 0.0

FIG. 8 (PRIOR ART)

Approved  
RJM





TITLE: ROBOT SYSTEM HAVING IMAGE  
PROCESSING FUNCTION  
INVENTORS: Atsushi WATANABE, et al.  
SERIAL NO.: 09/546,392  
DOCKET NO.: 392.1681

FIG.10 (PRIOR ART)

Approved  
RJH

